



GENERAL DRAWING NOTES: U.O.S.

- BREAK ALL CORNERS 0.030 RADIUS OR CHAMFER
- MACHINE ALL FILLETS 0.030 RADIUS
- ALL DIAMETERS CONCENTRIC -A- .005 TIR
- TURNED SURFACE FINISHES 63 RMS OR BETTER
- DRILLED OR BROACHED DETAILS 125 RMS OR BETTER
- DIM AND TOL SHALL BE HELD AFTER PLATING
- STAMP PART & WORK NUMBERS AS SHOWN
- DO NOT USE DRAWING IF MANF. HOLD IS INITIALED

SCHMITT INDUSTRIES, INC.
 2765 NW NICOLAI ST., PORTLAND, OR 97210
 TEL: (503) 227-7908 FAX: (503) 223-1258

REVISION HISTORY - (MOST CURRENT REV. AT TOP)

TOLERANCES: **UNLESS OTHERWISE SPECIFIED**

PART: **IASERcHECK 6212 HEAD**

X.XX = +/- 0.010 [X.XX] = +/- [0.05]
 X.XXX = +/- 0.005 [X.X] = +/- [0.1]
 ANGLES = +/- 1.0 DEG. [X] = +/- [0.3]

NUMBER: **YYL006212** FILE: **YYL006212.idw** SHEET: 1

SCALE: **NONE** MATERIAL:
Do Not Scale Drawing

DATE: **4/25/11** DRAWN BY: **MEC** MANF. HOLD: HOLD DATE: